

Saville PowerLite Wide

WX-3700

New high brightness, widescreen projector with network capability and many professional features.



- Contrast ratio 500:1
- Audio alarm for security feature
- On start / auto input search / Power-OFF and GO
- Easy maintenance / lamp replacement / air filter
- Free positioning (360° pitching)
- Customised logo screen
- Networkable (Wireless 11b/g / Wired)
- SD card "Viewer" function

WX-3700

WXGA

3700 lumens

3.7kg

Widescreen
Installation

Specification

Brightness	up to 3700 ANSI Lumens	Computer: Higher Resolutions	Displayed panned or Smart Compressed
Illumination	Uniformity 85%	Computer: Lower Resolutions	Displayed normal or Smart Expanded
Color Reproduction	10 bit/1.07 Billion Colors	Video Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Contrast Ratio	500:1 (Lamp mode "Auto" Image mode "Dynamic")	Video HD Compatibility	480i/p, 575i/p, 720p, 1035i, 1080i
Projection Lamp	275 Watt UHP	Formats Supported	Normal 4:3 and Wide Screen 16:9
Estimated Lamp Life	up to 3000 Hours of Use	Video: Image Sizing	Video Scaling Technology
Imaging System	0.74" PolySilicon active matrix TFT Panels x 3	Image Signal Inputs	
Screen Pixels	1280 x 800 in stripe configuration	Computer in 1:	Analog** or Digital, or Digital Video w/HDCP: DVI-I x 1
Total Pixels	3,072,000 ((1280 x 800) x 3)	Computer in 2:	Analog/Component Video*** HD15 x 1
Lens Type	Manual Zoom and Focus	Video in - Composite:	RCA x 1
Lens Specs	Speed: f:1.7 ~ 2.5; FL: 0.756 ~ 1.189 in. (19.2 ~ 30.2 mm)	S-Video:	S-Video x 1
Lens Ratios	Zoom Max:Min: 1.57:1; Throw:Width: 1.18 ~ 1.86:1	Audio Signal Inputs	
Image Diagonal	40 ~ 300 in. (101.6 ~ 762 cm)	Computer 1 & 2/Component (Stereo)	MiniStereo x 1
Image Width	2.82 ~ 20 ft. (0.67 ~ 6.1 m)	Composite/S-Video (Stereo)	RCA x 2
Throw Distance (tele~wide)	3.3 ~ 39.7 ft. (1.0 ~ 12.1 m)	Outputs	
Front Elevation	Up 8.9°	Computer Monitor:	HD15 x 1
Maximum Pitch	anywhere up to 360° off the horizontal axis	Audio (Stereo) - Variable Line:	MiniStereo x 1
Anti Keystone	Preset Image Offset, Ratio (Top:Bottom) 49:1	Sound - Amplifier (Mono):	1 Watt RMS
Vertical Keystone Correction	Digital: up to 40° up or down	Sound - Speaker:	1.1 in. (2.8 cm) x 1
Scanning Frequency	Auto: H Sync. 15-100kHz; V Sync. 50-100Hz	Fan Noise	as low as 30 dBA
Dot Clock	140 MHz	Cabinet Size (HxWxD)	3.07 x 13.15 x 10.3 in. (78 x 334 x 262 mm)
Image Orientation	Normal, Reversed, Inverted	Weight	8.2 lb. (3.7 kg)
Power Management	Auto Shutdown	Packaged Size (HxWxD)	10.0 x 16.0 x 14.8 in. (255 x 408 x 377 mm)
Remote Proj & Mouse Ctrl	(IR) Wireless/Wired with Laser Pointer x 1	Packaged Weight	14.5 lb. (6.6 kg)
Mouse Port	USB type B x 1	Power Requirements	100-240V AC, 50/60Hz
Wired Remote Control Port	MiniStereo x 1	Power Consumption	up to 390 W
Service Port (for RS-232 control)	Mini DIN 8 Pin x 1	Heat	up to 1331 BTU (335 KC)
Wired Network Port	RJ45 x 1 (100/10)	Power Cord	10' (3M) Type 3, Detachable
Computerless SlideShow Port	SD x 1	Electrical Safety Compliance	IEC/UL/cUL
Computer Native Resolution	1280 x 800 (WXGA)	Electromagnetic Compatibility	FCC Class B, CE Mark
Computer: Compatibility	UXGA (analog only)	Security Facilities	Kensington® Security Slot
	SXGA+, SXGA, WXGA, XGA, SVGA, VGA & MAC	Operating Temperature	41 ~ 95°F (5 ~ 35°C)
Computer: Formats	1600 x 1200 through 640 x 480	User Maintenance	Clean Air Filter, Replace Lamp

Saville Audio Visual Head Office: Millfield Lane, Nether Poppleton, York YO26 6PQ
Tel: 0870 606 1100 Fax: 01904 782700 E-mail: head.office@saville-av.com www.saville-av.com

saville
AUDIO VISUAL

FARNBOROUGH GUILDFORD WELWYN CARDIFF COVENTRY MANCHESTER LIVERPOOL LEEDS YORK HULL NORTH EAST EDINBURGH GLASGOW BELFAST